St. Louis County (C) McDonnell Douglas (Tract I)

RECEIVED

JUN 19 1996

IRCRA PERMITTING A CONFLIANCE BRANCH

STATE OF MISSOURI

Mel Carnahan, Governor • David A. Shorr, Director

DEPARTMENT OF NATURAL RESOURCES

DIVISION OF ENVIRONMENTAL QUALITY-

St. Louis Regional Office

10805 Sunset Office Drive, Suite 100 St. Louis, MO 63127-1017

(314)822-0101

FAX (31+)822-0943

DECEIVE

MAY 3 1996

April 25, 1996

Mr. Joseph Haake, Group Manager MISSOURI DEPARTMENT OF Environmental and Hazardous Materials Services NATURAL RESOURCES McDonnell Douglas Corporation Dept. 064C, Bldg. 110, MailCode 1111099
P.O. Box 516
St. Louis, MO 63166

Dear Mr. Haake:

L.O.W. #96-SL.015

Enclosed is a report of an inspection conducted by Mr. Joe Trunko of my staff. The section titled "UNSATISFACTORY FEATURES" lists violations noted during the inspection and outlines steps the inspector has determined will correct those violations.

By May 24, 1996, a written response must be submitted to this office that describes the actions taken to correct the unsatisfactory features noted in the report. Please direct the response to Mr. Joe Trunko. A copy of your response should also be forwarded to Ms. Kathy Flippin, Chief-Enforcement Unit, Hazardous Waste Program, P.O. Box 176, Jefferson City, MO 65102.

Should you have any questions, please call Mr. Trunko at (314) 822-0101.

Sincerely,

ST. LOUIS REGIONAL OFFICE

Robert S. P. Eck Regional Director

RSPE/JLT/jh

Enclosures

c: HWP

R00029901
RCRA Records Center

O

RESOURCE CONSERVATION AND RECOVER ACT
AND
MISSOURI HAZARDOUS WASTE MANAGEMENT LAW
COMPLIANCE EVALUATION INSPECTION REPORT

FACILITY

McDonnell Douglas Corporation Tract I P.O. Box 516 St. Louis, MO 63166 (314) 232-3319

EPA ID#: MOD000818963
MO Generator ID#: 001001
Permit #: OSO 062284 002
Resource Recovery #: 0268-A
MO Transporter ID#: H-1039

PARTICIPANTS

Missouri Department of Natural Resources (MDNR)

McDonnell Douglas Corporation

Joseph L. Trunko Environmental Specialist

Joseph Haake, Group Manager Environmental & Hazardous Materials Services

INTRODUCTION

On April 17, 1996, an inspection was conducted at McDonnell Douglas Corporation-Tract I (MCDC) located in St. Louis County, Missouri. The inspection was conducted under the authority of the Resource Conservation and Recovery Act (RCRA) of 1976 and Sections 260.375(9) and 260.377 of the Missouri Hazardous Waste Management Law (1977) as amended. The inspection was confined to facets of the facility operation related to hazardous waste management.

Storage Permit #OSO 062284 002, issued to MCDC on March 22, 1984, expired on June 22, 1994. A renewal Part B application was submitted to the Department. A technical review of the application started in August 1995.

FACILITY DESCRIPTION

MCDC is a manufacturer of military aircraft. Operations at the facility include chemical processing (conversion coating, etching, pickling, and electroplating), machining of parts, composite manufacturing, parts degreasing and painting, aircraft assembly and painting, aircraft testing (flight ramps), industrial wastewater pretreatment, and a boiler house.

MCDC operates five days per week, 24 hours per day, three shifts per day. A site map of the facility is attached.

MCDC is a large quantity generator of hazardous waste. Numerous waste streams are generated. However, the largest waste streams include corrosive waste, emulsified cutting oil, paint solids,

McDonnell Douglas - act I (HW) April 25, 1996 Page 2

solvent and paint waste, and wastewater treatment sludge. A summary of the hazardous waste streams generated at this facility is attached.

MCDC is also permitted to store hazardous waste for greater than 90 days. Waste generated from on-site as well as waste from off-site facilities is stored. Only waste from MCDC facilities is accepted from off-site. The waste accepted from off-site is similar to that described above. Hazardous waste is transported to Tract I by MCDC (Missouri Transporter ID #H-1039).

MCDC stores on-site generated waste (drum related) at three less-than-90-day storage areas. These areas are located on the east side of Building 2, at Building 48, and at Building 51, respectively. Waste solvents and paints are accumulated in satellite drums located at the paint shops in Buildings 2, 27, and 48. Oils are also accumulated at numerous satellite locations (mainly in Buildings 27, 29A, 220, 2, 42, and 48). When full, these containers are transferred to one of the less-than-90-day storage areas or directly to the permitted storage area. Waste oils generated in the general flight ramp area are stored at a separate storage shed located north of Building 40.

Solids contaminated with paint and/or solvents are accumulated in red, two cubic yard dumpsters. There are approximately 30-40 of these dumpsters located throughout the facility (mainly in Buildings 27, 220, 29, 2, 45, and 48). When full, these dumpsters are emptied into two compactor roll-offs located at the north side of Building 27 and the north side of Building 48, respectively (approximately twice per week). The roll-off containers are transported by Peoria Disposal Company to an off-site hazardous waste facility.

Solids that have been contaminated with solvents or paint are placed in 5, 10, 15, and 30-gallon red trash cans located at the immediate work areas. There are approximately 400-500 of these containers located throughout the facility. At the end of each shift, these cans are emptied into the nearest two-yard dumpster.

MCDC is currently initiating a plan to reduce the number of small accumulation containers. Many of the small containers (5, 10, and 15 gallon) will be eliminated and replaced with 30 gallon containers that will accumulate waste from larger work areas. This plan has already been implemented in Building 101 at Tract II and has been successful.

Wastewater pretreatment sludge (F006/F019) is accumulated in a 15 cubic yard roll-off container that is located underneath the filter press in Building 14. This waste is shipped directly off-site by Heritage Transport, Inc.

McDonnell Douglas act I (HW) April 25, 1996 Page 3

Waste coolant from manufacturing equipment is collected in portable tanks and is pumped into a storage tank located in the lower level of Building 27. The waste coolant is managed as a used oil and is shipped off-site by Heritage Transport, Inc.

MCDC currently stores hazardous waste for greater than 90 days in the following unit:

Building 27 Scrap Dock Container Storage Area - Containers from off-site and from the on-site, less-than-90-day storage areas are stored at this area. Acids, alkalis, oils, solvents, and paint sludges are stored in Area 1. Cyanides and sulfides are stored in Area 2, which consists of a prefabricated storage building. A staging area for the Container Storage Area has been constructed underneath the Building 39 overhang.

MCDC has submitted modifications requesting the removal of the storage tanks from the permit. A detailed description of these tanks was included in previous inspection reports. The current status of these tanks is as follows:

Building 14 Sludge Holding Tank - MCDC submitted a request to remove this tank from permit status based on the wastewater treatment exemption. Additional sampling was conducted around the tank and a final closure report was submitted to the Department.

Building 52 Caustic Tanks (H19, H20) - The tanks are currently used to store waste sodium hydroxide solution. The solution is sent to Reynolds Aluminum in Texas for use in their process. As a result, it is not considered a solid waste. Additional sampling was conducted around the tanks and a final closure report was submitted to the Department.

Building 52 Acid Tanks (H12-H16) - These tanks are currently used to store waste nitric hydrofluoric acid (pickling solution). This solution is sent to a facility in Washington, Missouri, that uses it as an ingredient in their process. As a result, it is not considered a solid waste. MCDC is pursuing closure of these tanks. Sampling conducted by MCDC around the tanks showed contamination. Additional sampling will be conducted to determine the extent of the contamination.

Hush House Waste Tank - Groundwater remediation is ongoing. Closure will not be certified until the cleanup levels specified by the Department are achieved. Waste jet fuel generated in this area is currently being run through an oil water separator.

Fuel Pit #3 and #4 Waste Tanks - Same as the Hush House Waste Tank.

Ramp Station 1 and 2 Waste Tank - Tank has been removed.

Groundwater remediation is ongoing. Waste jet fuel generated in this area is currently being run through an oil water separator.

McDonnell Douglas-act I (HW) April 25, 1996 Page 4

The following units have been certified closed and are no longer part of the permit:

Building 52 Acid Tanks (H1-H6)
Building 6 Waste Oil Tank
F-18 Silencer Waste Tank
Building 27 Scrap Dock Container Storage Area 2 (original area 2)
Building 28 Waste Tank
Building 10 Explosives Storage Building

Waste jet fuel generated at this facility is burned as a fuel in the facility's boilers. As a result, the jet fuel is not considered a solid waste.

MCDC has a Resource Recovery Certification (expires November 18, 1996) for the following operations:

Distillation of spent Methyl Ethyl Ketone (MEK) and Methyl Isobutyl Ketone (MIBK) at the Building 27 and Building 48 paint areas. The distillation unit located at the paint area in Building 27 has been removed due to its age and deteriorating performance. The distillation unit located at the Building 48 paint area was moved to the large paint shop in Building 2. The unit is currently not being used.

The recovery of perchloroethylene by steam stripping carbon adsorption beds. This process is located in Building 51. Prior to chemical milling, a maskant coating that contains perchloroethylene is applied to metal parts. As the parts dry, the perchloroethylene evaporates, is collected, and is run through a carbon adsorption unit. The perchloroethylene is stripped from the carbon beds with steam and is collected for reuse as an ingredient in new maskant production.

The recovery of used hydraulic oil. Used hydraulic oil generated from metal fabrication equipment in building 29 is processed through a thermo-vacuum-distillation unit. Water and solids are removed from the oil and the oil is reused at the facility. This activity no longer requires resource recovery certification.

Solid waste generated at the facility is hauled by MCDC to the Westlake Sanitary Landfill. Burnable solid waste is collected in brown, 2 cubic yard dumpsters and is burned in a permitted incinerator located at the MCDC Tract II facility.

MCDC has a NPDES Permit (MO-0004782) from the MDNR for the discharge of storm water and non-contact cooling water.

McDonnell Douglas-act I (HW) April 25, 1996 Page 5

MCDC has a corporate goal to reduce the quantity of hazardous waste generated at this facility by 90 percent over the period 1987 to 2000. The facility recently began segregating empty paint cans from the paint solids waste stream and ship them offsite for recycling. MCDC is also considering additional on-site neutralization of corrosive waste streams.

UNSATISFACTORY FEATURES

Satellite containers of hazardous waste not marked and dated, in violation of 10 CSR 25-5.262(2)(C)3. The following satellite accumulation containers were not marked or dated: a 55-gallon drum of waste solvent in the Building 27 paint area; a 55-gallon drum of waste solvent in the Building 2 large paint area; two 30-gallon drums of paint solids in the Building 48 paint area.

All satellite accumulation containers of hazardous waste must be marked with the words "HAZARDOUS WASTE," or with other words that identify the contents of the containers, as well as with the beginning date of satellite storage. Mr. Haake informed the employees working at the paint areas of the marking/dating requirements and the proper labels were attached to the containers during the inspection.

2. The storage of hazardous waste in the permitted area for over one year, in violation of 10 CSR 25-5.265(1) incorporating 40 CFR 268.50(c). A review of the computer tracking log for the permitted container storage area indicated that approximately 60 containers have been stored in Area 1 for over one year.

The Land Disposal Restrictions only allow the storage of hazardous waste at a permitted facility for up to one year. However, hazardous waste may be stored for over one year if such storage was solely for the purpose of accumulation of such quantities of hazardous waste as are necessary to facilitate proper recovery, treatment, or disposal. MCDC must dispose of all hazardous waste that has been stored for over one year at the facility or must submit information to the Department that shows this length of storage was necessary in order to facilitate proper recovery, treatment, or disposal.

3. Failure to obtain approval for a change in the resource recovery operation, in violation of 10 CSR 25-9.020(3)(E)1. The distillation unit located at the Building 48 paint area was moved to the Building 2 large paint area in December 1995. The unit was inactive at the time of the inspection, but will be utilized at this area in the future.

McDonnell Douglas-act I (HW) April 25, 1996 Page 6

MCDC must submit a written notification to the Hazardous Waste Program describing the modification to the resource recovery process. Please address the notification to Mr. Dave Maschler of the Hazardous Waste Program. A copy of the notification should also be sent to this office.

COMMENTS

An area to stage and process drums prior to placement in the permitted storage area has been designated under the Building 39 overhang. The area is enclosed by an asphalt berm. MCDC must calculate the capacity of the containment system in order to determine the maximum quantity of containers that may be stored in this area. The capacity of the containment system must be at least 10 percent of the waste volume or the volume of the largest container, whichever is larger. This information must be submitted to this office.

PREPARED BY:

Joseph L. Trunko

Environmental Specialist

APPROVED BY:

Mike Struckhoff

Unit Chief, Hazardous Waste

JLT/jh

| | | - | |
|---|----|------|--|
| ī | 00 | 1510 | |

LOG PAGE 1 OI

MISSOURI DEPARTMENT OF NATURAL RESOURCES HAZARDOUS WASTE PROGRAM LARGE QUANTITY GENERATOR INSPECTION RECORD AND CHECKLIST FOR FACILITIES THAT GENERATE/ACCUMULATE > 1000 Kg (2.200 lbs. or approximately, 5 drums) EPA I D. NUMBER 4 - 17-96 McDomell Douglas Corporation - Tract I MOD000818 963 MO LD NUMBER ADDRESS 001001 P.O. Box 516 0268-A TELEPHONE NUMBER NUMBER OF EMPLOYEES YEARS AT SITE (314) 232 - 3319 St. Louis 6,500 FACILITY REPRESENTATIVE(S), TITLE(S) Joe Hacke - Group Munager, Emironmental and Hazardeus Makrials Services DESCRIPTION OF THE FACILITY'S OPERATIONS AND PLANT. Included in Written Report

| WASTE STREAMS | 1 1100 | THE CONTRACT OF THE PERSON NAMED IN | 0.75 |
|---|--------------------|-------------------------------------|-------------|
| DESCRIBE EACH WASTE STREAM GENERATED INCLUDING THE PRODUCTION PROCESS | GENERATION RATE | EPA ID NUMBER | DISPOSITION |
| 1. | | | |
| 2. Included in Written Report | | | |
| 3. | | | |
| 4. | | • | |
| 5 | | | |
| CHECK ALL THAT APPLY (Specify if possible) | | | e i ja ja |
| NRDEC Barries Disad/Acid Batteries POTW | | | |

Septic Tank

Air Permit

MO 780-0854 (7-92)

☐ Solid Waste Landfill .

Waste Water Pretreatment

| A. GENERAL | | |
|---|-------|---|
| 1. Registered as a HW Generator - Section 260.380.1 (1) RSMo and 10 CSR 25-5.262 (2)(A) | GGR | COMMENTS |
| 2. Facility determines if waste is hazardous - 10 CSR 25-5.262(1) incorporating 40 CFR 262.11 | GGR | |
| 3. Utilizes a licensed hazardous waste transporter - Section 260.380.1 (5) RSMo | GGR | |
| 4. Utilizes authorized HW TSD or RR facility - Section 260.380.1(7) RSMo | | |
| 5. Facility does not operate as a TSD - Section 260.390(1) RSMo | GGR | |
| PART 1: WALK-THROU | GH IN | SPECTION |
| B. PRETRANSPORT, CONTAINERIZATION & STORAGE | | |
| 1. Storage does not exceed 90 days or 180/270 days if facility generates \$\inf 1000 \text{ Kg/month} - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a) | GPT | COMMENTS |
| 2. Containers in good condition - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.171 | GPT | |
| 3. Waste compatible with container - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.172 | GPT | |
| 4. Containers closed in storage - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.173(a) | GPT | ••• |
| 5. Containers storing incompatible waste separated or protected from each other by a dike, berm or wall - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.177(c) | GPT | |
| 6. Container storage areas have a containment system if holding more than 1000 Kg of liquid hazardous waste - 10 CSR 25-5.262 (2)(C)2.B.(I) | GOR | |
| 7. Base of containment system is imprevious and free of cracks or gaps - 10 CSR 25-5.262 (2)(C)2.B.(III)(a). | GOR | |
| 8. Containers protected from contact with accumulated liquids - 10 CSR 25-5.262(2)(C)2.B.(III)(b). | GOR | |
| Capacity of containment system = 10% of waste volume or volume of largest container, whichever is greater - 10 CSR 25-5.262(2)(C)2.B.(III)(c). | GOR | |
| 10. Run-on onto the containment system is prevented or excess capacity is provided - 10 CSR 25-5.262(2)(C)2.B.(III)(d). | GOR | |
| 11. Accumulated liquids removed to prevent overflow of containment - 10 CSR 25-5.262(2)(C)2.B.(III)(e). | GOR | |
| 12. Containers of ignitable or reactive waste stored >50 ft. from property line (or meet requirements) - 10 CSR 25-5.262(2)(C)5. referencing 40 CFR 265.176 as amended by 10 CSR 25-7.265(2)(I)7.and 8. | GPT | • |
| 13. Containers clearly marked "hazardous waste" - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(3) | GPT | |
| 14. Waste packaged/labeled/marked per DOT during entire on-site storage period - 10 CSR 25-5.262(2)(C)1. | GOR | 5 · · · · · · · · · · · · · · · · · · · |
| 15. Date of accumulation marked on containers - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(2) | GPT | |
| 16. Facility inspected and maintained (weekly) - 10 CSR 25-5.262(2)(C)2.A.(I) and (II) referencing 40 CFR 265.174 | GPT | |
| 17. Daily inspection of areas subject to spills, i.e., waste handling areas - 10 CSR 25-5.262(2)(C)2.A.(II) | GOR | |
| 18. Adequate aisle space is available - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.35 | GPT | |
| 19. Placards available for transporter - 10 CSR 25-5.262(1) incorporating 40 CFR 262.33 | GPT | |
| 20. Tho Smoking signs conspicuously placed by ignitable or reactive wastes - 10 CSR 25-5.262(2)(C)2.D(II) | GOR | |
| 21. Waste oil containers in good condition, labeled and closed - 10 CSF 25-11.010(3)(C) | GOR | |
| SATELLITE ACCUMULATION | | |
| 1. Containers kept closed - 10 CSR 25-5.262(1) incorporating 40 CFF 262.34(c)(1)(i) referencing 40 CFR 265.173(a) | GPT | COMMENTS |
| - portial// W// respectively | | 100 PAGE 2 |

| . O Contai | ners in good condition | - 10 CSR 25-5.262(1) inco | orporating 40 | GPT | COMMENTS | |
|---|--|--|--|--|---|---------------------|
| Waste | 62.34(c)(1)(i) referencing compatible with contain 3 262.34(c)(1)(i) reference | ner - 10 CSR 25-5.262(1) i | ncorporating | GPT | | |
| Quanti | ties accumulated not e | exceeding 55 gal. (1 quar CSR 25-5.262(1) in | t of acutely- corporating | GPT | | |
| Satelli | | rage within 3 days of filli | ng - 10 CSR | GPT | | |
| ontai | | contents & beginning date | - 10 CSR 25- | GOR | | |
| | | an 1 year - 10 CSR 25-5.26 | 52(2)(C)3. | GOR | | |
| | | ENTION AND EMERGE | | DURE | S | |
| Facilit | v operated and mainta | ined to minimize the pos 2(1) incorporating 40 CFF | sibility of an | GPT | COMMENTS | |
| Adequequip | ate and proper spill | control, decontamination sets, respirators, SCBA, abs | n and safety sorbents, etc.) | GPT | | |
| Adequ | rate water supply and fire | e control equipment - 10 CS a)(4) referencing 40 CFR 2 | SR 25-5.262(1) 65.32(c) & (d) | GPT | m coc has assite fire / emergency responded to emerge | وسائ وسائد الافح |
| Device emer | e in the hazardous wast | e operation area capable o 10 CSR 25-5.262(1) in | of summoning | GPT | | • |
| fire o | hone or two-way radio or police department R 262.34(a)(4) referencie | on-site and capable of sun - 10 CSR 25-5.262(1) i ng 40 CFR 265.32(b) | nmoning local incorporating | GPT | | |
| Comm | nunication and emerger | ncy equipment tested and | maintained - | | | |
| CFR 2 | 265.33 | ating 40 CFR 262.34(a)(4) | referencing 40 | GPT | | 1 - 97 T |
| LQG TA | 265.33 | CONTENTS | capaci | | CONTAINMENT | AG |
| CFR 2 LOG TA TANK | NKS DESIGNATION No Hazardous | CONTENTS waste strage in | CAPACI | TY | | 1 |
| LOG TA TANK | NKS DESIGNATION No Hazardous | CONTENTS waste storage in (HIZ-HIB) are u | CAPACI tanks | TY re u | containment whe nitric hydrofleuric acid prier | |
| TANK | NKS DESIGNATION No Hazardous Siding 52 Tank | CONTENTS Whish strage in (HIZ-HIB) are us shipment offish | CAPACI towks sed to ste to fer reuse | TY re u | stere west sodium by drexide soli | to |
| TANK C | DESIGNATION No Hazardous Sidny 52 Tank | CONTENTS Waste strage in (HIZ-HIB) are us shipment offision the tanks (HIP, H | CAPACI towks sed to ste the for reuse 120) are use | TY re u re u re u | stere weste sodium hydrexide soli | to |
| TANK TANK Spill disco | DESIGNATION No Hazardous Sciding 52 Tank Building 52 Cav Building 14 Sludge prevention controls in point couplings - 10 Cav | CONTENTS Weste storage in s (Hi2-Hib) are u shipment official thic tanks (HI9, H prior to ship ment tank is part of lace and operating e.g. ch SR 25-5262(1) incorpor | CAPACI towks sed to state for reuse and are use washwater eck valves, dry | TY Te construction of the | stere weste sodium hydrexide soli | to |
| TANK TANK 2. Spill 3. disco | DESIGNATION No Hazardous Sidny 52 Tank Building 52 Tank Building 14 Sludy prevention controls in point couplings 10 Cau (a) (1) referencing 40 Cau (iii) prevention controls is, automatic feed cutof | CONTENTS Likes to strange in Shipment official the tanks (H19, H prior to ship ment etank is part of lace and operating e.g. ch SR 25-5.262(1) incorpor FR 265.194(b)(1) | CAPACI towks sed to ste se for reuse 100) are use offsite for waskwater eck valves, dry ating 402 CFR e.g. high: level incorporating | TY Te construction of the | stere weste sodium hydrexide solice. | to |
| TANK TANK Spill disco 262.3 Cover alarm 40°C Suffice CSR | DESIGNATION No Hazardaus Sidny 52 Tank Building 52 (av Building 53 (av Building 14 51 av Building 14 av Building 14 51 av Building 14 av Building 14 51 av Building 14 51 av Building 14 av Buildi | CONTENTS Liks to strage in Shipment official the tanks (H19, H prior to ship ment e tank is part of lace and operating e.g. ch SR 25-5.262(1) incorpor FR 265.194(b)(1) | CAPACI towkS sed to ste se for reuse eck valves dry ating 40: CFR e.g. high level incorporating rertopping 3 10 | TY Per la | stere weste sodium hydrexide solice. | to |
| TANK TANK TANK Spill disco | Position of the second of the | CONTENTS Like strage IN Shipment official Shipment official Takes (H19, H prior to ship ment I ace and operating e.g. ch SR 25-5.262(1) incorpor FR 265.194(b)(1): In place and operating J. etc. 10 CSR 25-5.262(1) Ing. 40 CFR 265:194(b)(2) wered lanks to prevent ovaling 40 CFR 262:34(a) compatible with tank 10 C (a)(1) referencing 40 CFR | CAPACI CAPACI | TY GPT GPT GPT | stere weste sodium hydrexide solice. | to |
| TANK TANK TANK Spill disco 262.3 Over alarm 40.C Wass Wass Inco inco | DESIGNATION No Hazardaus Didny 52 Tank Building 52 Tank Building 53 (au Building 14 Sludy prevention controls in point couplings 10 C (a) (1) referencing 40 C (iii) prevention controls is, automatic feed cutof FR 262.34(a) (1) reference cient freeboard in uncontrols FR 265.194(b) (3) te or treatment method of porating 40 CFR 262.34 mpatible wastes not plan rporating 40 CFR 262.34 | CONTENTS Lich te strage in Shipment official Shi | CAPACI CAPACI | TY GPT GPT GPT | stere weste sodium hydrexide solice. | to |
| TANK 1. 2. 3. 4. 5. 1. Spill discourse alarm 40°C 2. Over alarm 40°C 3. Suffi CSR 40°C 40°C | DESIGNATION No Hazardaus Didny 52 Tank Building 52 Tank Building 53 (au Building 53 (au Building 14 Study prevention controls in pount couplings 10 (au Building 14 Study prevention controls in pount couplings 10 (au Building 14 Study prevention controls in pount couplings 10 (au Building 14 Study prevention controls in pount couplings 10 (au Building 14 Study Building 14 Stud | CONTENTS Like strage IN Shipment official Shipment official Tanks (HI9, H prior to ship ment thank is part of lace and operating e.g. ch SR 25-5-262(1) incorpor FR 265-194(b)(1)(2) In place and operating In plac | CAPACI CAPACI | TY GPT GPT GPT GPT GPT | stere weste sodium by drexide solvestored | to |

| 8. [| | Volatiles with vapor pressure > 78 mm @ 25° C not placed in open tanks - 10 CSR 25-5.262(2)(C)2.D.(I) | GOR | |
|------|---|---|-----|-----|
| 80 | 1 | Wastes and residues removed as hazardous waste and tank and equipment decontaminated upon closure - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.197(a). | GPT | |
| 10. | | Secondary containment system provided for tanks and equipment; installed after July 14, 1986; storing dioxin waste; over 15 years old; of unknown age in facility over 15 years old; repaired, replaced or reinstalled after July 14, 1986 - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(a) | GPT | |
| 11. | 3 | Secondary containment system constructed of or lined with impervious waste compatible material - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(c)(1) | GPT | |
| 12. | 2 | Containment system supported by base capable of preventing failure due to settlement, compression or uplift - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(c)(2) | GPT | |
| 13. | 7 | Containment system provided with a leak detection system capable of detecting a release within 24 hours - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(c)(3) | GPT | |
| 14. | 7 | Containment system sloped or designed to drain and remove liquids - 10 CSR 25-5.262(2)(C)2.C. referencing 10 CSR 25-5.262(2)(C)2.B. (III)(b) | GOR | |
| 15. | 3 | Containment system capable of containing 100% of the capacity of the largest tank - 10 CSR 25-5.262(2)(C)2.C. referencing 10 CSR 25-5.262(2)(C)2.B.(III)(c) | GOR | |
| 16. | 3 | Containment system free of cracks or gaps - 10 CSR 25-5.262(2)(C)2.C. referencing 10 CSR 25-5.262(2)(C)2.B. (III)(a) | GOR | |
| 17. | T | Run-on onto containment system prevented or excess capacity is provided - 10 CSR 25-5.262(2)(C)2.C. referencing 10 CSR 25-5.262(2)(C)2.B.(III)(d) | GOR | |
| id. | Image: section of the content of the | Spilled or leaked waste and precipitation removed from secondary containment within 24 hours or as soon as possible - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(c)(4) | GPT | |
| 19. | ď | Tanks are clearly labeled or marked "Hazardous Waste" - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(3) | GPT | |
| 20. | <u> I</u> | Daily inspections of overfill/spill control equipment, aboveground portions of tank system, secondary containment, and data gathered from monitoring equipment - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.195(a) | GPT | • 1 |
| 21. | 3 | Inspection log maintained - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.195(c) | GPT | |
| 22. | 3 | Cathodic protection systems inspected annually, impressed current sources every two months - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.195(b) | | |
| 23. | 3 | engineer for tanks installed after July 14, 1986, prepared and on-site- 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.192 | GPT | |
| 24. | ! | Written assessment by an independent, qualified, professional engineer prepared and on-site for tanks lacking secondary containment 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.191 | CPT | |
| 25. | | Leak test, internal inspection or tank integrity exam performed annually and documented, by an independent, qualified, professional engineer for tanks lacking secondary containment - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.193(i) | GPT | |
| 26. | | Leak/spill response resulted in: waste flow stopped immediately; waste removal; containment and removal of visible releases to the environment; notification and report; and repair or closure - 10 CSF 25-5.262(1) incorporating 40 CFR 262.34(a)(1) referencing 40 CFR 265.196 | GPT | |

COMMENTS

PART 2: RECORDS INSPECTION

| | IANIFESTS | Witte. | |
|----------------|--|-------------------|----------|
| 1. { | Facility uses manifest system - 260.380.1.(6) RSMo, and 10 CSR 25- 5.262(2)(B) | GMR | COMMENTS |
| 2. | Records maintained for a 3-year period - 10 CSR 25-5.262(1) incorporating 40 CFR 262.40(a) | GRR | |
| 3. | Generator's MO & EPA I.D. Numbers - 10 CSR 25-5.262(2)(B) | GOR | |
| 4. | Manifest document, ID and consecutive shipment numbers - 10 CSR 25-5.262(2)(B)2.A. | GOR | * |
| 5. | Generator's name, address and phone number - 10 CSR 25-5.262(2)(B)2. | GMR | |
| 6. | All transporters' names, phone numbers, MO & EPA I.D.#'s, license plate # - 10 CSR 25-5.262(2)(B)2. | GMR | 6 |
| 7. | Designated facility name, address, phone, MO & EPA I.D. #, - 10 CSR 25-5.262(2)(B)2. | GMR | |
| 8. | DOT shipping name, Hazard Class and waste I.D. # (RQ - if required) - 10 CSR 25-5.262(2)(B)2. | GMR | 8 |
| 9. | Containers, quantity and specific gravity designated - 10 CSR 25-5.262(2)(B)2. | GMR | |
| 0. | Manifest signed and dated - 10 CSR 25-5.262(2)(B)2. | GMR | |
| 1. | Out of state manifests have all required MO information - 10 CSR /25-5.262(2)(B)4.A. | GOR | ā |
| 2. | Manifest continuation sheets are not used - 10 CSR 25-5.262(2)(B)1. | GOR | |
| 3. | Manifest returned within 35 days - or exception report submitted within 45 days - 10 CSR 25-5.262(2)(D)2.C. | GRR | · |
| 13 | Summary Manifest Reports and manifest copies sent to DNR quarterly - 10 CSR 25-5.262(2)(D)1. | GOR | |
| G. | AND DISPOSAL RESTRICTIONS | 16.00 | COMMENTS |
| 1 | Tests waste or uses knowledge of waste to determine it the waste is restricted from land disposal 4.10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a) | GLB | COMMENTS |
| 2: | Dilution of waste to meet LDR treatment standards is not occurring 10 CSR 25-7-268(1) incorporating 40 CFR 268.3(a) | GLB | |
| | "Land-Ban" notification/certification, sent with manifests and retained on-site for five years - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a) | 000 | |
| 4. | Notification/certification includes correct EPA Hazardous Waste number, corresponding treatment standards, manifest number, and waste analysis data - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a) | GLB | |
| | <u> </u> | | |
| | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) | | 21 |
| | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) PERSONNEL TRAINING | GLB | |
| н. | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) | GLB | COMMENTS |
| H. 1. | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) PERSONNEL TRAINING Personnel are trained to respond to emergencies including the use of alarm systems, emergency equipment and contingency plan - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR | GLB | COMMENTS |
| H. 1. | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) PERSONNEL TRAINING Personnel are trained to respond to emergencies including the use of alarm systems, emergency equipment and contingency plan - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(a)(3). Employees do not work in unsupervised positions until they have completed the training - 10 CSR 25-5.262(1) incorporating 40 CFR | GLB GPT GPT | COMMENTS |
| H. 1. 2. | waste in tanks or containers to meet LDR treatment standards - 10 CSR 25-7.268(1) incorporating 40 CFR 268.7(a)(4) Personnel are trained to respond to emergencies including the use of alarm systems, emergency equipment and contingency plan - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(a)(3). Employees do not work in unsupervised positions until they have completed the training - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(b) Training reviewed annually - 10 CSR 25-5.262(1) incorporating 40 CFR | GPT GPT | COMMENTS |

| 6. Gives job title, job description and name of employee filling each position - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(d)(1) and (2) | GPT | COMMENTS |
|--|----------|-------------------------------------|
| 7. Written description of introductory and continuing training that will be given to each position - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(d)(3) | GPT | |
| 8. Documentation of training completed by personnel - 10 CSR 25-5.262(t) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(d)(4) | GPT | |
| 9. Records of current personnel maintained until facility closure, former employee records maintained for at least three years - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.16(e) | GPT | 2 |
| I. CONTINGENCY PLAN | | |
| 1. Contingency plan maintained on-site - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.53(a). | GPT | COMMENTS |
| 2. Plan submitted to local emergency response agencies - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.53(b) | GPT | |
| 3. Emergency coordinator on-site or on call - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.55 | GPT | |
| 4. Plan describes actions personnel must take in response to fires, explosions or other releases of hazardous waste - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(a) | GPT | |
| 5. Describes arrangements with emergency response agencies - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(c) | GPT | |
| 6. Lists names, addresses and phone numbers (home and office) of emergency coordinators - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(d) | GPT | = 7 |
| Primary emergency coordinator designated - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(d) | GPT | |
| 8. List emergency equipment including description, location and capabilities - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(e) | GPT | |
| 9. Evacuation plan, if applicable, designates primary and secondary routes and evacuation signal - 10 CSR 25-5.262(1) incorporating 40 CFR 262.34(a)(4) referencing 40 CFR 265.52(f) | GPT | |
| J. WASTE OIL | | |
| 1. Waste oil is managed properly and not disposed of into the environment | GOR | COMMENTS |
| 2. Listed hazardous waste mixed with waste oil is handled as a hazardous waste 10 CSR 25-11.010(1)(C)2. | GOR | |
| 3. Registered as waste oil generator if gen./accum. 220 lb 10 CSR 25-11.010(2)(A) | GOR | |
| 4. Written waste oil contract maintained - 10 CSR 25-11.010(4)(C) | GOR | |
| 5. Uses a licensed transorter and receiving facility - 10 CSR 25-11.010(4) | GOR | |
| C. RESOURCE RECOVERY | W N | |
| 1. RR certification for energy recovery or reclamation of waste oil or | GOR | COMMENTS |
| hazardous waste on-site - 10 CSR 25-9.020(1)(A)32-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2- | GOR | |
| 3. Facility is classified as U, R1 or R2 accurately - 10 CSR 25-9.020(3)(A). | GOR | |
| Facility meets the operating conditions of certification - 10 CSR 25-9.020(30)(E)3. | GOR | |
| Facility has submitted a written request and received approval from the DNR for all changes in operation including closure - 10 CSR | GOR | relocated to Bldg 2 large part area |
| 25-9.020(3)(E) 1. and 2. | <u> </u> | LOG PAGE 6 C |

| 6. [| Facility report submitted to DNR quarterly - 10 CSR 25-9.020(3)(E)6. referencing 10 CSR 25-7.264(2)(E)3. | GOR | COMMENTS |
|-------|---|---------|--|
| 7. | Facility maintains a written operating record - 10 CSR 25-9.020(3)(E)5. referencing 40 CFR 264.73(b)(1) & (2) as modified by 10 CSR 25-7.264(2)(E)2. | GOR | |
| 8. [| Facility has notified EPA and the state that it qualifies for a small quantity on-site burner exemption or has interim status or a permit if it burns hazardous waste on-site - 10 CSR 25-7.266(1) incorporating 40 CFR 266.108 and 40 CFR 266.103. | 000 | |
| 9. [| R2 facility uses an adequate sampling and analysis plan to assess incoming shipments - 10 CSR 25-9.020(3)(C)1. | GOR | * |
| 10. [| R2 facility maintains a daily log of manifest number, wastes received, disposition of waste and corresponding sampling data - 10 CSR 25-9.020(3)(C)2. | GOR | à |
| 11. [| R2 facility has a written closure plan which meets 40 CFR 264.112 requirements - 10 CSR 25-9.020(3)(C)3. | GOR | e e |
| 12. [| R2 facility provides financial assurance for closure - 10 CSR 25-9.020(3)(C)4. | GOR | |
| CHE | CKLIST KEY | | W W |
| | ck the 🗹 if in compliance. | | |
| Circ | le the if not in compliance and provide comment. | | |
| N/A | = Not Applicable | | |
| | naded item is a serious deviation from the requirements (Class I v | iolatic | |
| | | | |
| Anι | unshaded item is a significant deviation from the requirements (C | lass II | violation unless conditions warrant Class I) |
| 71/ | IMENTS: INCLUDE DISCUSSION OF FACILITY'S WASTE MINIMIZATION PL | AN | |
| Ė | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | £2 2 | |
| | | | 47 |
| | | | |
| | 9 | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | • |
| | | | |
| | | | |
| | \wedge | | |
| INSPE | ECTOR'S SIGNATURE | | DATE |
| | | | 4 17 91 |

MO 780-0854 (7-92)

4-11-96

HAZARDOUS WALLE TREATMENT/STORAGE/DISPOSAL FALLITY

| | PERMITTED PHOTOTTY CHE | CKETST |
|-----------------------|--|---|
| Name of Facility: | na Dannell Dauglas Corporation - Trust | Date <u>4-17-96</u> |
| Address: P.O. Bc | x 516 | Missouri I.D. # 001001 |
| McDe- | mell Bld. Stilouis, Mo 63166 | EPA I.D. # MOD 000318763 |
| Facility Representati | ve: Jee Hnake | Transporter? <u>Ves</u> , # <u>H-1039</u> |
| Tit | 12: Group Manager - Environmental and Hozardous Materials Services | Phone Number (314) 032-3319 |
| Provide a brief descr | ription of the treatment, storage | or disposal process, if the process |
| has changed from the | description in the permit applic | ation. |
| | | |
| | | |
| | Included IN Written Repo | ct |
| | | |
| | · | |
| List the hazardous wa | stes, if any, that are not liste | d in the application or permit but |
| that are found being | treated, stored, disposed or rec | ycled: |
| | | |
| <u>Waste</u> | Amount/Month Kilo | gram/Month I.D.# Disposition |
| 1, | 2 | |
| 2 | Included in written Rep | art |
| 3, | | <u> </u> |
| 4, | | |
| | Total | |
| Are the manifest(s) a | and quarterly summary reports bei | ng completed and filed with the |
| | | rson City, MO. 65102 as required. |
| | yes <u> </u> | |

The following numbering system corporates the state and federa litations. The state citations to the regulations appears at the top of each section. The last part of the state citation refers to the part of 10 CFR, the federal regulation. In the column, the federal regulation appears as a period and number, .XX. The more stringent state regulations appear in parenthesis, ().

| 10 CSI | R 25-5.262 Standards for Generators (General/Standard/Special) Condition |
|--------|---|
| . 1 | Generator's MO and EPA I.D. Numbers |
| (2) | 8) No more than 10 days time between generator and facility signatures(\checkmark |
| (2) | 32) Serially Increasing shipment number |
| | Generator's name, address, phone # |
| | All transporters' names, phone #'s, MO and EPA I.D. #'s |
| | Designated facility name, address, phone # and EPA I.D. # |
| | Proper DOT Shipping Name, Hazard Class and I.D. # \checkmark |
| | Containers, Quantity and Unit Wt/Vol being shipped properly designated(\checkmark) |
| (28 | 6) Proper certification(/ |
| (23 | 6) Manifests returned within 35 days(🗸 |
| (2E | 6) Completed manifests submitted to DNR quarterly |
| .23 | Manifest properly signed by generator/transporter/TSD and dated(\checkmark |
| (20 | 1) Summary Manifests Report submitted to DNR quarterly |
| (20 | 2) Exception generator report submitted within 45 days |
| . 41 | Biennial Report(У |
| ,3¢ | Waste stored in proper DOT containers $ec{\mathcal{S}}$ |
| .32 | Containers/Tanks labeled "Hazardous Waste" and labeled per proper DOT |
| | requirements during storage(\square |
| , 33 | Placards available for use by transporters \checkmark |
| (20 |) Facility inspected and maintained(${\cal A}$ |
| | Ignitable and reactive wastes properly handled \checkmark |
| | Date of accumulation marked,(\checkmark_1 |
| | Storage less than 90 days (if applicable)(4) |
| (20 | 2) Satellite Accumulation requirements met (if applicable) \ldots \checkmark |
| | Stored in satellite areas less than 1 year |
| | Container marked identifying contents and beginning date |
| | Containers kept closed / compatible / good condition |
| | Quantities accumulated not exceeding 55 gal. (1 quart acutely hz waste).($ec{	extstyle s}$ |
| | |

10 CSR 25-7,264(2)(B) General Fig. Lity Standard (General/Standard Special) Condition ____

| .16 Pe | rsonnel training |
|------------------|--|
| (E.) | Completed classroom or on-the-job training to handle emergencies($ec{ec{ec{v}}}$ |
|) (<u>F</u> .) | 2) Trainer qualified in hazardous waste management procedures documented($ec{ee}$ |
| (€) | Annual review of training(الم |
| (占) | Job title, description, and name of person filling position(イ |
| (⇌) | Written record of the type and amount of training given |
| ,17 Ge | eneral Requirements for Ignitable, Reactive or Incompatible Wastes |
| (E) | Precautions taken to prevent accidental ignition |
| (b) | Precautions taken to prevent reaction |
| (;) | Documented methods used(🗸 |
| .18 Lo | cation Standard |
| (b) | Floodplains - plan in place for how facility will remove wastes from |
| | areas that could be flooded |
| 0 CSR 25- | 7.264(2)(C) Preparedness and Prevention (General/Standard/Special) Condition |
| | |
| .32(a) | Internal communication or alarm system |
| (b) | Device in the hazardous waste operation area capable of summoning |
| | emergency assistance(🗸) |
| (∈) | Fire control, spill control, and decontamination equipment available(\checkmark |
| (년) | Adequate water supply for fire control equipment |
| .33(a) | Adequate and proper safety equipment, available and ready(|
| .34 Ea | ch person in hazardous waste area able to summon help $ec{ec{ec{ec{ec{ec{verta}}}}}$ |
| .35 Ad | equate aisle space(У |
| .37 Ar | rangements with local emergency agencies(🧹 |
| | (Facility has onsite fire /emergency response dept.) |

| 10 CSR 25-7. | .264(2)(D) Contingen Plan | (General/Standar Special) Condition |
|--------------|--|--|
| * | | |
| ,51 Has | contingency plan been used suc- | cessfully(イ |
| .52 Are | following items up-to-date | |
| (a) D | etailed description of procedu | res that personnel must implement |
| i | n response to fires, explosion | s, releases of hazardous waste(🗸 |
| | | ncy services \checkmark |
| | | (home & office) of emergency coordinator(s)(/) |
| | | ts description and location |
| | | ······································ |
| .53 Copy | of the contingency plan at sign | te |
| ,54 Cont | ingency plan need amendments ma | ade as necessary(\square |
| .55 Emer | gency coordinator can commit $r_{\rm c}$ | esources in an emergency \checkmark |
| .56 Emer | gency coordinator can explain (| nis responsibilities in emergency situations |
| (Use | the exit interview to ask spec | cific questions about possible emergencies |
| at s | it=,), | ······································ |
| | | |
| | | |
| | | |
| | | 20 |
| 10 CSR 25-7. | 264(2)E) Manifest System (Gener | ral/Standard/Special) Condition |
| | | |
| | f Manifest System (wask rece | ived from MCOC facilities only) |
| | ite facilities | |
| (a)(1) | | r/transporter/TSD and dated(/) |
| (a)(2) | and the participant of the market to be a con- | ads noted \checkmark |
| (a)(3) | | ······································ |
| (a)(4) | Copy to generator in 30 days, | ر ۱۰۰۰ میلی در |
| (a)(5) | Copy at facility for 3 years, | ٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠ |

(c) Use Generator Checklist for waste sent off-site 10 CSR 25-5.262......

| Operati | ng Record | | |
|---------|-------------------------------------|-------------------------------------|--|
| .72(a) | Manifest properly | signed and dated | ············ |
| (년) | Completed manifest | ts submitted to DNR quarterly | , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |
| (∈) | Summary Manifest F | Report submitted to DNR quarterly | |
| (占) | Biennial Report | | |
| .73(a) | Description, quant | city, and TSD process for all hazar | dous wastes(🗸 |
| (₽)(| Location and qu | uantity of all hazardous waste | ······································ |
| (b)(| Waste analysis | records from off-site sources | |
| (占)(| 4) Summary and des | scription of emergency incidents | · · · · · · · · · · · · · · · · · · · |
| (Б)(| 5) Record of inspe | ections | |
| (占)(| Monitoring and | testing and analytical results on- | site if necessary(V |
| Reporti | ſιg | | |
| .74 Re | conds are kept and | available for inspection | |
| .75 Qu | arterly facility re | ports submitted | |
| (2G) | Ground water moni | toring data on-site/submitted | h |
| (2H) | Certification of | information signed | |
| .76 Un | manifested waste re | ports for off-site facilities on-s | ite/submitted(⊀ |
| .77 Re | ports for emergenci | es, spills, closure on-site/submit | ted,(|
| | | | |

LING

| 10 CSF | R 25-7.264(2)(G) Closure d Post-Closure (General/Standar Special) Condition |
|------------|--|
| .11 | 12 There is a copy of the approved closure and post-closure plans onsite(|
| | tank and Aump Steition I and a truk are all undergoing closure. |
| | |
| 10 CSF | R 25-7.264(2)(H) Financial Requirements (General/Standard/Special) Condition |
| .14 | for closure, post-closure, and sudden and non sudden liability |
| 10 CSR | 25-7.264(2)(I) Use and Management of Containers (General/Std/Special) Condition |
| ,17 ,17 | 2 Containers made of materials compatible with hazardous wastes placed in them.(\checkmark |
| , 17 | inspection log completed |
| | |
| .17 | 6 Ignitable or reactive waste at least 50 ft. from property line(ゾ 7(a) Incompatible wastes placed in different containers(ゾ (c) Containers holding incompatible wastes separated by dikes, or walls(ゾ |


(No this it storage in tamks)

4-17-96


Date

| | (J)(1.) | No hazardous waste having a vapor pressure of 78 mm of Hg at 2 | 5°C in an |
|------|-------------|--|---|
| | | open tank | |
| | .194(a) | No hazardous waste shall be placed in tank if it causes a fail | , |
| | ,194 (B) | o/o uses appropriate practices to prevent spills (one of the fo | |
| | (1) | spill prevention devices | _ |
| | | overfill prevention devices | |
| | | maintain sufficient freeboard | |
| | | f spill facility complied with 264.196 | |
| | | verfill controls inspected | |
| | | he following components are inspected daily | , |
| | | above ground portions of tanks | (./. |
| | | data from leak detection equipment | |
| | | area around tank to check for leaks | |
| | | thodic protection and integrity of tank(s) inspected | |
| | | within 6 months of installation and annually thereafter | 156 |
| 85 | | all sources of impressed current must be inspected every other | |
| | | spections documented in operating record | |
| | | The second secon | |
| | | | |
| | | | 21 |
| (1 | In complian | ce (—) In violation | |
| | ector's nam | | _ |
| Titi | | Environmental Specialist I | _ |
| | | | |

FORM FERMIT-INSPEC (MARCH 1988)



McDonnell Douglas Aerospace (Tract I)
MOD 000 818963
001001
050 062234002



| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|---|---|--------------------|---|---------------------|
| | B.27-158B, Tank 51, Plating Area Ammonia Persulfate | RQ, Waste Corrosive Liquids, N.O.S. (Ammonia Persulfate) 8, UN1760, PG II (D002) ERG # 60 | D006 | Chrome | 1.0 |
| 003 | B.27-158B, Tank 49, Plating Tanks Nitric/Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | D006 | | 1.0 |
| 93 | B.27-162, Tank S-2, Aluminum Line Nitric Acid/Sodium Dichromate | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Chromic Acid) 8, UN1760, PG II (D002) ERG # 60 | D007 | Lead, Nickel | 1.20 |
| 008 (a) | B.27-162, Tank 7, Aluminum Line Nitric Acid/Amehem 7/Amchem 17 Replenisher | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Chromic Acid) 8, UN1760, PG II (D002/D007) ERG # 60 | | | 1.16 |
| 008 (b) | B.27-162, Tank 18, Aluminum Line Nitric Acid/Amehem 7/Amchem 17 Replenisher | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Chromic Acid) 8, UN1760, PG II (D002/D007) ERG # 60 | | | 1.05 |
| 010 (a) | B. 27-158B, Tank 38, Plating Area Sulfuric Acid , Sod. Dichromate | RQ, Waste Sulfuric Acid, Spent 8, UN1832, PG II (D002) ERG # 39 | D006/D007 | Selenium | 1.10 |
| 010 (b) | B.27-162, Tank J, Aluminum Line Sulfuric Acid w/Chrome | RQ, Waste Sulfuric Acid, Spent 8, UN1832, PG II (D002) ERG # 39 | D007 | | 1.23 |
| 010 (c) | 8.27-162, Tank K, Aluminum Line Sulfuric Acid w/ Chrome | RQ, Waste Sulfuric Acid, Spent 8, UN1832, PG II (D002) ERG # 39 | D007 | | 1.18 |
| 10 (d) | B.27-162, Tank T-5, Titanium Line Sulfuric Acid w/Chrome | RQ, Waste Sulfuric Acid, Spent 8, UN1832, PG II (D002) ERG # 39 | D007 | Nickel, Lead | 1.19 |
| 012 (a) | B.27-162, Tank 3, Aluminum Line Nitric/HF Acid | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric Acid) 8, UN1760, PG II (D002) ERG # 60 | D007 | | 1.25 |
| 012 (b) | B.27-162, Tank T-8, Titanium Line Nitric/HF Acid | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric Acid) 8, UN1760, PG II (D002) ERG # 60 | D007 | Cadmium, Lead, Nickel | 1.49 |
| 013 (a) | B. 27-158B, Tank 22, Plating Area Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | D006 | Nickel | 1.07 |
| 013(b) | B. 27-162, Tank 11, Aluminum Line Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D007) ERG # 60 | | | .97 |

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|---|--|--------------------|---|---------------------|
| 013 (c) | B.27-158B, Tank 2, Plating Tanks Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | D006/D008 | | 1.20 |
| 013 (d) | B.27-158B, Tank 3, Plating Tanks Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | D006/D008 | | 1.10 |
|)13 (e) | B.27-158B, Tank 4, Plating Area Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | D006 | Silver, Barium, Nickel | 1.18 |
| 013 (f) | B.27-162, Tank 5, Aluminum Line Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002/D007) ERG # 60 | | | 1.07 |
| 013 (g) | B.27-162, Tank 9, Aluminum Line Chromic Acid | RQ, Waste Chromic Acid Solution 8, UN1755, PG II (D002) ERG # 60 | D005/D007 | | 1.01 |
| 016 (a) | B.27-158B, Tank 9, Plating Area Hydrochloric Acid | RQ, Waste Hydrochloric Acid, Solution 8, UN1789, PG II (D002) ERG # 60 | D006/D007/ D008 | Nickel | 1.10 |
| 016 (b) | B.27-158B, Tank 28, Plating Area Hydrochloric Acid | RQ, Waste Hydrochloric Acid, Solution 8, UN1789, PG II (D002) ERG # 60 | D006 | Chromium | 1.03 |
| 017 | B.27-158B, Tank 15, Plating Area Ammonia Nitrate | Hazardous Waste, Liquid, N.O.S., (Ammonia Nitrate Solution) 9, NA3082, PG III (D006) ERG # 31 | | | 1.09 |
| 121 | B.27-158B, Tank 33, Plating Area Sulfuric/ HF Acids | RQ, Waste Corrosive liquids, N.O.S. (Sulfuric/Hydrofluoric Acid) 8, UN1760, PG III (D002) ERG # 60 | D004/D006/ D007 | Nickel | 1.22 |
| 023 (a) | B. 27-162, Tank S5, Aluminum Line Nitric Acid | RQ, Waste Nitric Acid Solution 8, UN2031, PG II (D002) ERG # 44 | D007 | Lead | 1.49 |
| 023 (b) | B.27-158B, Tank 40, Plating Area Nitric Acid | RQ, Waste Nitric Acid Solution 8, UN2031, PG II (D002) ERG # 44 | D006/D007/ D008 | Nickel | .99 |
| 023 (c) | B.27-162, Tank T-9, Titanium Line Nitric Acid | RQ, Waste Nitric Acid Solution 8, UN2031, PG II (D002) ERG # 44 | D006/D007 | Lead, Nickel | 1.26 |
| 024 (a) | B.27-158B, Tank 12, Plating Area Sodium Hydroxide w/Chrome | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002/D007/D008) ERG # 60 | D006 | Nickel | 1.09 |

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|--|--|--------------------|---|---------------------|
| 024 (b) | B.27-158B, Tank 14, Aluminum Line Sodium Hydroxide w/Chrome | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II | D006/D007/ D008 | N/A | 1.3 |
| 024 (c) | B.27-158B, Tanks 10 & 30, Plating Area Sodium Hydroxiode w/Chrome | (D002) ERG # 60 RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | D006/D007/ D008 | | 1.0 |
| 24 (d) | B.27-162, Tank T-1, Titanium Line Sodium Hydroxide w/Chrome | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | D007 | Lead, Nickel | 1.25 |
| 025 (a) | B.27-162, Tank 20, Aluminum Line Sodium Hydroxide Non-Hazardous | Sodium Hydroxide Solution 8, UN1824, PG II ERG # 60 | | | 1.01 |
| 025 (b) | B.27-162, Tank T-2, Titianium Line Sodium Hydroxide Solution (No Chrome) | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # | | Chrome | 1.61 |
| 028 | B.27-162, Tank M, Aluminum Line Potassium Dichromate | Hazardous Waste, Liquid, N.O.S (Potassium Dichromate Solution) 9, NA3082, PG III (D007) ERG # 31 | <u></u> | | 1.04 |
| 029 (a) | B.27-162, Tank 1, Aluminum Line Sodium Tetraborate Non-Hazardous | Waste Caustic Alkali Liquids, N.O.S. (Sodium Tetraborate) 8, UN1719, PG II ERG # 60 | D007 | | 1.02 |
| 029 (b) | B.27-162, Tank F, Aluminum Line Sodium Tetraborate | Waste Caustic Alkali Liquids, N.O.S. (Sodium Tetraborate) 8, UN1719, PG II ERG # 60 | | Chrome | 1.03 |
| `38 | Red Dumpster Waste | RQ, Hazardous Waste Solid, N.O.S. (Paint/Solvent Contaminated Material) 9, NA3077, PG III, (D007) ERG # 31 | F002/F003/ F005 | F002-TCE F003, MIBK, Xylene F005-MEK, Toluene | 1.01 |
| 041 (a) | Chlorinated Solvents | RQ, Halogenated Irritating Liquids, N.O.S. (Use Specific Chlorinated Solvents) 6.1, UN1610, PGIII, (D040/F002) ERG # 58 | demonstration | | 1.3 |
| 041 (b) | Trichloroethylene (TCE) | RQ, Waste Trichloroethylene 6.1, UN1710, PGIII (D040/F001) Vapor Degreaser (D040/F002) Non-Vapor Degreaser ERG # 74 | | 144 | 1.3 |
| 042 (a) | Waste Jet Fuel | RQ, Waste Fuel, Aviation, Turbine Engine 3, UN1863, PG II (D001)ERG # 27 | | | .80 |

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|---|---|-------------------------------------|--|---------------------|
| 042 (b) | Jet Fuel Off-Spec | Fuel, Aviation, Turbine Engine 3, UN1863, PGII () ERG # 27 | | | .80 |
| 043 | Flammable Solvent/Paint Waste | RQ, Waste Paint Related Material 3, UN1263, PG III (D001/D007) ERG # 26 | D035/F002 F003/F005 | F002-Methylene Chloride, Trichloroethane F003-Ethyl Acetate, N-Butyll, Alcohol, MIBK, Ethylbenzene, Xylene, Cyclohexanone, Butyl Acetate, Methanol, Acetone F005-MEK, Toluene, Benzene, Isbutyl Alcohol | .99 |
| 044 (b) | Used Oil | Used Oil Non-Regulated | | | 1.05 |
| 045 | Flammable/Chlorinated Solvents | RQ, Waste Flammable Liquids, N.O.S. (Flammable/Chlorinated Solvents)3, UN1993, PGII (D001/D007) ERG # 26 | D035/D039 D040/F002 F003/F005 | F002- Trichloroethane, Trichloroethylene, Methylene Chloride, Chlorobenzene F003-Ethyl Acetate, N-Butyl, Alcohol, MIBK, Ethylbenzene, Xylene, Cyclohexanone, Methanol, Acetone, Ether Ether F005-MEK, Toluene, Isbutyl Alcohol | 1.01 |
| 047 | Chlorinated Oil | Hazardous Waste, Liquid, N.O.S (Oil Contaminated with Chlorinated Solvents) 9, NA3082, PG III, () ERG # 31 | D035/D039 D040/F002 F003/F005 | F002- Trichloroethane, Trichloroethylene F003- MIBK, Xylene, Cyclohexanone, F005-MEK | .98 |
| 053 | Acid, Alkaline Spill Clean-up | RQ, Waste Corrosive Solids, N.O.S. (Use Specific Chemical)8, UN1759, PGII (D002) ERG # 60 | | | 1.5 |
| 056 | B.27-158B, Tank 35, Plating Area Ethylene Diamine, Nitric, Sulfonic Acid Solution | Hazardous Waste, Liquid, N.O.S. (Nitric/Sulfonic Acid Solution) 9, NA3082, PG III (D006) ERG # 31 | | Silver, Chromium, Nickel | 1.19 |
| 080 | Tract I Flammable Lab-Pack | RQ, Waste Flammable Liquids, N.O.S. (Flammable Laboratory Chemicals-Lab Pack) 3, UN1993, PG II, (D001) ERG # 27 | | | |
| 080 | Tract I Corrosive Lab-Pack | RQ, Waste Corrosive Liquids, N.O.S. (Corrosive Laboratory Chemicals-Lab Pack) 8, UN1760, PG II, (D002) ERG # 60 | | | |
| 082 | B.27-162, Tank T-6, Titanium Line | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric/Phosphoric Acid) 8, UN1760, PG II, (D002) ERG # 60 | D004/D007 | Cadmium, Nickel | 1.37 |

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|-------|---|--|--------------------|---|---------------------|
| 091 | Acid Sludge | RQ, Waste Corrosive Solids, N.O.S. (Use Specific Acid Sludge) 8, UN1759, PG II (D002) ERG # 60 | Use Tank Code | (Use tank elements) | 1.32 |
| 092 | Alkaline Sludge | RQ, Waste Corrosive Solids, N.O.S. (Use Specific Alkaline Chemical) 8, UN1759, PG II (D002) ERG # 60 | Use Tank Code | 50 80 | 2.10 |
|)26 | B. 27-158B, Tank 24, Plating Area Sulfuric Nickel/Boric Acid | Waste Nickel Solution Non-hazardous | | | 1.13 |
| 026 | B.27-158B, Tank 27A, Plating Area Tanks 17, 27A, 46 Sodium Cyanide/Cadmium Solution | RQ, Waste Corrosive Liquid, Poisonous, N.O.S. (Sodium Cyanide) 8, UN2922, PGII (D003/D006) ERG # 59 | D007/F007 | F | 1.08 |

Hazardous Waste Streams and Shipping Names Tract I - South & Remotes Sites

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|---|--|--------------------|---|---------------------|
| | B.52, Tank S1 Ammonia Bifluoride Solution | Hazardous Waste, Liquid, N.O.S. (Ammonia Biflouride Solution) 9, NA3082 PG III () ERG # 31 | D004 | Mercury | 1.01 |
| 003 | B.220, Tank D Nitric Chromic Acid, Passajell | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Chromic Acid) 8, UN1760, PG II (D002, D007) ERG # 60 | D008 | Nickel | 1.17 |
| 010 | B.220, Tank 5 Sulfuric Acid/Pott. Dichromate (Chrome) | RQ, Waste Sulfuric Acid, Spent 8, UN1832, PG II (D002/D007) ERG # 39 | D008 | Nickel | 1.28 |
| 012 (a) | B.52, Tank T-3 Nitric/HF Acid Alumium Desmut | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric Acid) 8, UN1760, PG II (D002) ERG # 60 | D007/D008 | Nickel | 1.21 |
| 012 (b) | B.52, Tank S3 Nitric/HF Acid Titanium Pickle | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric Acid) 8, UN1760, PG II (D002) ERG # 60 | D004/D007/ D008 | Cadmium, Nickel | 1.32 |
| 012 (c) | B.52, Tank S5 Nitric/HF Acid Titanium Pickle | RQ, Waste Corrosive Liquids, N.O.S. (Nitric/Hydrofluoric Acid) 8, UN1760, PG II (D002) ERG # 60 | D007/D008 | Cadmium, Nickel | 1.36 |
| 024 | B.220, Tank A Turco ARR/Sodium Hydroxide (Contains Chrome) | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | D007 | Silver, Nickel, Lead | 1.24 |
| 025 (a) | B.2, Level 1, Dept. 126B Sodium Hydroxide Solution (Non- Hazardous) | Sodium Hydroxide Solution 8, UN1824, PG II () ERG #60 | | | 1.04 |
| 025 (b) | B.72-442E Sodium Hydroxide (No-Chrome) | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | | Chrome, Silver | 1.11 |
| 029 (a) | B. 220, Tank 2 Turco 4215S Sodium Tetraborate | Hazardous Waste, Liquid, N.O.S. (Sodium Tetraborate) 9, NA 3082, PGIII ERG # 31 | D007 | | 1.03 |
| 029 (b) | B.245-431-4 Sodium Tetraborate | Non-Hazardous Per Annual | | | 1.08 |
| 035 (a) | B.52, Tank T-1 Sodium Hydroxide | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | D007 | Silver, Mercury | 1.35 |
| 035 (b) | B.52, Tank T-6 Sodium Hydroxide | RQ, Waste Sodium Hydroxide Solution 8, UN1824, PG II (D002) ERG # 60 | D007 | | 1.36 |

Hazardous Waste Streams and Shipping Names Tract I - South & Remotes Sites

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|---------|--|--|---------------------------------------|--|---------------------|
| 036 | B.14, WWT Plant Wastewater Treatment Sludge | RQ, Hazardous Waste, Solid, N.O.S. (Wastewater Pretreatment Sludge) 9, NA3077, PG III (F006, F019) ERG # 31 | | Chromium | 1.01 |
| 037 (a) | B. 2, Level 1, Oil Crib V. S. 653 | Used Emulsified Cutting Oil Non-Regulated | | | 1.05 |
| 037 (b) | B.276-444 Bio-cool 500 | Used Emulsified Cutting Oil Non-Regulated | | | .99 |
| 38 | Red Dumpster Waste | RQ, Hazardous Waste, Solid, N.O.S. (Paint/Solvent Contaminated Material) 9, NA3077, PG III, (D007) ERG # 31 | F002/F003/ F005 | F002- TCE F003- MIBK, Xylene F005- MEK, Toluene | 1.01 |
| 041 | Chlorinated Solvents | RQ, Halogenated Irritating Liquids, N. O.S. (Specific Chemical) 6.1, UN1610, PGIII (D040/F002) ERG # 58 | | 8 | 1.3 |
| 041 | Trichloroethylene (TCE) | RQ, Waste Trichloroethylene 6.1, UN1710, PGIII (D040/F001) Vapor Degreaser (D040/F002) Non-Vapor Degreaser ERG # 74 | | | 1.3 |
| 042 (a) | Waste Jet Fuel | RQ, Waste Fuel, Aviation, Turbine Engine 3, UN1863, PGII (D001) ERG # 27 | (1 -1) | | .80 |
| 042 (b) | Jet Fuel Off Spec | Fuel, Aviation, Turbine Engine 3, UN1863, PGII ERG # 27 | | | .80 |
| 043 | Flammable Solvent/Paint Waste | RQ, Waste Paint Related Material 3, UN1263, PG III (D001/D007) ERG # 26 | D035/F002/ F003/F005 | F002-Methylene Chloride, Trichloroethane F003-Ethyl Acetate, N-Butyll, Alcohol, MIBK, Ethylbenzene, Xylene, Cyclohexanone, Butyl Acetate, Methanol, Acetone F005-MEK, Toluene, Benzene, Isbutyl Alcohol | .99 |
| 044 | Tract I South Used Oil | Non-regulated Used Oil | | | |
| 045 | Flammable/Chlorinated Solvents | RQ, Waste Flammable Liquids, N.O.S. (Flammable, Chlorinated Solvents) 3, UN1993, PGII (D001/D007) ERG # 26 | D035/D039/ D040/F002/ F003/F005 | F002- Trichloroethane, Trichloroethylene, Methylene Chloride Chlorobenzene F003-Ethyl Acetate, N-Butyl, Alcohol, MIBK, Ethylbenzene, Xylene, Cyclohexanone, Methanol, Acetone, Ether Ether F005-MEK, Toluene, Isbutyl Alcohol | 1.01 |

Hazardous Waste Streams and Shipping Names Tract I - South & Remotes Sites

| MO ID | Product/Tank Usage Area | Proper Shipping Name | Other EPA Codes | HAZ Constituents/ Underlined HAZ Constituents | Specific Gravity |
|-------|--|--|---------------------------------------|--|---------------------|
| 047 | Chlorinated Oil | Hazardous Waste, Liquid, N.O. S. (Oil Contaminated with Chlorinated Solvents) 9, NA3082, PGIII, () ERG # 31 | D035/D039/ D040/F002/ F003/F005 | F002- Trichloroethane, Trichloroethylene F003- MIBK, Ethylbenzene, Xylene, Cyclohexanone, Methanol, Acetone, Ether Ether F005-MEK | .98 |
| 053 | Acid/Alkaline Spill Clean-Up | RQ, Waste Corrosive Solids, N.O.S. (Use Specific Chemical) 8, UN1759, PGII (D002) ERG # 60 | | | 1.5 |
| J75 | B.220-180 Calcium Hydroxide (System 7 Mold Material) | RQ, Waste Corrosive Liquids, N.O.S. (Calcium Hydroxide) 8, UN1760, PG II (D002) ERG # 60 | | | 1.23 |
| 080 | Corrosive Lab-Pack | RQ, Waste Corrosive Liquids, N.O.S (Corrosive Laboratory Chemicals-Lab Pack) 8, UN1760, PG II, (D002) ERG # 60 | | | |
| 080 | Flammable Lab-Pack | RQ, Waste Flammable Liquids, N.O.S., (Flammable Laboratory Chemicals-Lab Pack) 3, UN1993, PG II, (D001) ERG # 27 | | | |
| 095 | 2 Level 1-126B Formic/Gluconic Acid/HF | RQ, Waste Corrosive Liquids, N.O.S. (Hydrofluoric Acid, Formic Acid) 8, UN1760, PG II, (D002) ERG # 60 | | Barium, Cadmium, Chrome | 1.08 |
| 098 | B. 276, Dept. 444 V. S. 759 | Waste Coolant | , | | .99 |